




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 9/445	A1	(11) International Publication Number: WO 00/36502 (43) International Publication Date: 22 June 2000 (22.06.00)
(21) International Application Number: PCT/US98/27924 (22) International Filing Date: 20 January 1998 (20.01.98) (71) Applicant: SIEMENS BUSINESS COMMUNICATION SYSTEMS, INC. [US/US]; 4900 Old Ironsides Drive, Santa Clara, CA 95052 (US). (72) Inventor: BEYDA, William, J.; 21580 Edward Way, Cupertino, CA 95014 (US). (74) Agents: SMITH, Darryl, A. et al.; Siemens Corporation, Intellectual Property Dept., 186 Wood Avenue South, Iselin, NJ 08830 (US).		(81) Designated States: CA, CN, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: AN AUTOCONFIGURABLE METHOD AND SYSTEM HAVING AUTOMATED DOWNLOADING



(57) Abstract

A method of upgrading a system, such as a computer, that supports a variety of devices includes locating and identifying a first supported device and determining location information related to a remote site at which device-level software is stored. The determination of location information is an automated response to identifying the first device and the device-level software at the remote site is specific to the identified device. The remote site is automatically accessed via transmission lines. The device-level software is then downloaded from the remote site to the system. In the preferred embodiment, the automated process that frees the user from intervention is carried to the installation of the downloaded software and the autoconfiguration of system resources. For personal computers, the downloaded software is typically driver software.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

AN AUTOCONFIGURABLE METHOD AND SYSTEM HAVING AUTOMATED DOWNLOADING

BACKGROUND OF THE INVENTION

The invention relates generally to a method and system that
5 require different drivers to enable different devices supported by the system,
and relates more particularly to automating such a system.

DESCRIPTION OF THE RELATED ART

The addition of an internal adapter card or a peripheral device to
10 a computer typically requires a reconfiguration of the system resources of the
computer. This requirement that the computer must be configured to allocate
specific system resources to specific devices significantly increases the
complexity of upgrading the computer. If two or more devices attempt to
utilize the same resource, a hardware and/or software conflict will occur. The
15 system resources that must be allocated include direct memory access (DMA)
channels, interrupt request lines (IRQs), memory locations for driver software,
and input/output (I/O) memory addresses. Often, physically installing an add-
on device is relatively simple, but the reconfiguration of system resources
requires expertise that exceeds the capabilities of typical users.

20 In an attempt to simplify upgrades of computer systems,
autoconfiguration technology has received increasing attention. The
autoconfiguration technology is sometimes referred to as "plug-and-play
technology." The user merely physically installs the device and the computer
automatically configures itself in a manner that prevents conflicts. For
25 example, the microprocessor of a personal computer may communicate with
the various devices that the computer supports in order to determine which
devices are installed, what resources are available for allocation, and what
resources are required by the installed devices. The system is then able to
determine an acceptable allocation.

30 While it is not critical to the implementation of the
autoconfiguration technology, there are preferably four interacting
components to an autoconfiguration process. The first component is the

device that is to be added. The device may be a peripheral, an adapter card, or the like. In a plug-and-play environment, the device should be able to identify itself to the other components of the autoconfiguration process and preferably have resource assignments that can be changed depending upon conflict resolutions. A second component is the basic input/output system (BIOS) of the computer. The BIOS can locate, configure and activate the various devices. A third component is the operating system that discovers and resolves resource conflicts. The fourth component is a non-volatile random access memory that stores the configuration data during times in which the computer is shut down. If one or more of the four components are not designed to cooperate with other components to provide plug-and-play capability, the remaining components should be capable of compensating for the absence.

The autoconfiguration technology may be implemented in a number of manners. As an example, the BIOS may check the system bus to determine what devices exist. In a personal computer, the system bus may be an Industry Standard Architecture (ISA) bus, or may be an Extended Industry Standard Architecture (EISA) bus. The BIOS may disable some of the devices, while activating all boot devices. The operating system is then loaded. During the system boot up, the operating system determines the resource requirements of all of the devices and activates the non-boot devices. Preferably, all hardware and/or software conflicts are resolved during the boot up procedure. Any required device drivers are loaded into memory. If an add-on device has been detected by the BIOS, the operating system is notified by the BIOS. The configuration table that has been stored in the non-volatile random access memory is consulted to determine what resources can be allocated to the add-on device and/or whether resources that were previously allocated to existing devices need to be reallocated. A new configuration table can then be stored in the non-volatile random access memory.

In the design of a system or an add-on device that is to cooperate in providing autoconfiguration capability, forward compatibility is

typically the issue. That is, system and board designers attempt to accommodate future upgrades that may be installed at a later time. However, backward compatibility is also a concern. For example, when the operating system sold by Microsoft Corporation under the federally registered trademark
5 WINDOWS is upgraded from version 3.1 to WINDOWS95, a driver for a video accelerator board may cause reduced or improper performance. Installing a replacement driver that is specific to the video accelerator board and the upgraded operating system may be required to return performance to at least its original level.

- 10 For a computer system that supports a variety of devices, a version upgrade of the operating system may require the user to contact a number of different manufacturers in order to obtain the latest driver software. Many manufacturers maintain network sites that can be accessed via telecommunications lines, permitting users to download available drivers.
- 15 However, this requires users to possess the expertise to locate the network sites, contact the sites, and download the appropriate driver. For many users, the downloading requirement may defeat the purpose of the plug-and-play technology. This may even be true for situations in which a single driver is to be downloaded from an Internet site, e.g., when the driver software packaged
20 with a particular computer hardware component includes a "bug" that has been fixed by the hardware manufacturer since the packaging of the hardware was shipped by the manufacturer.

- What is needed is a system for supporting a number of devices and a method that facilitates system upgrades, preferably within an
25 autoconfiguration environment.

SUMMARY OF THE INVENTION

- A method of upgrading a system that supports a variety of devices, such as adapter boards, includes at least partially automating a
30 procedure for downloading device-level software for operating the supported devices. The upgrade procedure includes steps of identifying the first device that is supported by the system and, as an automated response to identifying

the first device, determining location information related to a remote site at which the device-level software is stored. In the preferred embodiment, the location information is a network site that is accessed via transmission lines and the device-level software is driver software specific to the identified first device. As an automated response to determining the location information, the system accesses the remote site. The device-level software is then downloaded from the remote site to the system in which the software is to be installed. If the system upgrade is an upgrade of the operating system of a computer, in one embodiment, a second device is then located and identified, so that the automated process can be repeated in obtaining the appropriate device-level software for the second device. In another embodiment, all of the devices are identified and the relevant remote sites are automatically determined before the network is accessed to download the various pieces of board-level software. The automated process of identifying and accessing a remote site in order to facilitate system upgrades applies to other multi-device systems in which there is a required association between a particular device and specific board-level software.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a system for executing system upgrades in accordance with the invention.

Fig. 2 is a flow chart of steps that are executed in using the system of Fig. 1.

DETAILED DESCRIPTION

An automated method of upgrading a system includes recognizing a system-supported device as being one that requires device-specific software, identifying a remote site at which the software is stored, accessing the remote site via transmission lines, downloading the device-specific software, and installing the device and the software properly. At least some and preferably all of the steps are implemented without a requirement of user intervention. Preferably, the method is executed within a

system that is designed for autoconfiguration of system resources, so that any resource conflicts among different devices are resolved without requiring user intervention.

At the time of installing an add-on device or at the time of upgrading an operating system, the system detects and identifies the device using autoconfiguration technology, which is also referred to as "plug-and-play technology." Typically, the add-on device of concern includes a requirement of installing hardware, but this is not critical. The automated process also may be utilized to locate and download a "driver" for an application program that requires specific system resources and requires a particular association with other software in order to operate properly.

As an automated response to detecting and identifying the device, a remote site is identified. The location information may be an address of an Internet site. For example, driver software may be stored for access via a site on the World Wide Web (WWW) for downloading by means of File Transfer Protocol (FTP). Alternatively, the site may be a bulletin board that is maintained by the vendor of the device of concern.

The automated system establishes communication with the remote site via a telecommunications line. This may be accomplished by means of a modem or an interface to an ISDN or other digital network. The established communication allows driver software to be downloaded. In the preferred embodiment, the downloading is accomplished without user intervention. When the method is utilized within the autoconfiguration environment, the downloaded software may be automatically installed using techniques known by persons skilled in the art.

The preferred embodiment utilizes the automated method with a personal computer. However, this is not critical. Any system that includes the sophistication to require identification of a specific association between a device and a particular piece of software can utilize the method. For example, a private branch exchange (PBX) that is attached to a network can automatically download the latest version of board-level software from a manufacturer when a new board is installed, such as when a line card is

added. The technique of automatically accessing a remote site that is maintained by a vendor of computer hardware may also be used in other applications. For example, the steps of identifying a particular remote site and automatically initiating communication between a system and the remote site may be used in the registration procedure. That is, after a device has been installed into a personal computer, the computer may automatically contact a vendor-maintained site that requires a user to input the information required for registering the product. Foreseeably, the registration information may be obtained directly from computer memory. This requires some interrogation of the personal computer by the vendor-maintained site. In another embodiment, the vendor-maintained site interrogates the personal computer to determine the proper resource allocation. This embodiment is beneficial if the personal computer is not designed to provide full auto-configuration capability. In still another embodiment, the automated method is utilized as a user's response to a suspicion or determination that board-level software includes a "bug." For example, if a device is operating improperly, the user may initiate the automated process by requesting a software "refresh" to identify the remote site and download the appropriate device-level software. Thus, if the vendor of the device has recently upgraded the device-level software to address the "bug," the upgraded software will be automatically downloaded to the user's system.

Referring now to Fig. 1, an exemplary system 10 for implementing the automated downloading process is shown. The system includes a conventional Basic Input/Output System (BIOS) 12. The BIOS is connected to access the bus or buses 14. The bus may be a conventional EISA bus, but other known buses having different addressing protocols may be utilized. The bus logically supports various devices 16, 18 and 20. Often, the bus also physically supports the devices, such as in circumstances in which adapter cards are inserted into board slots that provide the bus connections. However, the devices may also be connected to the bus 14 via cables.

An operating system 22 also functions in a manner well known

in the art. The type of operating system is not critical. The operating system 22 includes a number of modules. The two modules that are most relevant to the automated downloading process are shown in Fig. 1. A configuration manager 24 controls resource allocation to the various devices 16, 18 and 20.

5 The resources that must be properly allocated in order to avoid conflicts include interrupt request, I/O and memory addresses, and direct memory access channels. As will be explained more fully below, when a conflict-free configuration has been determined, the configuration is stored as a resource table 26 in non-volatile random access memory. Consequently, the

10 information from the resource table 26 is available each time that the system 10 is booted.

An autoconfiguration component 28 performs the functions provided by autoconfiguration technology. In one embodiment of autoconfiguration, a device locator 30 identifies one of the devices 16, 18 or 20. For

15 example, if the first device 16 has been added since the last boot up of the system 10, the device locator 30 identifies the first device. The first device is then "interrogated" in order to determine resource requirements of the device. If no potential conflicts exist, the autoconfiguration component 28 passes the resource requirements to the configuration manager 24, and an updated

20 resource table 26 is stored in non-volatile random access memory. On the other hand, if the system requirements of the first device 16 are unavailable, a resource arbitrator 32 is activated. The resource arbitrator calculates a configuration that is designed to avoid conflicts during operation of the system 10. At times, this requires the reassignment of resources that were previously

25 allocated to other devices 18 and 20. When an acceptable allocation is determined, the configuration is submitted to the configuration manager 24, which generates an updated resource table 26.

The autoconfiguration component 28 may be responsive to the BIOS 12 or the operating system 22, but is preferably able to cooperate with

30 both. That is, the configuration of system resources preferably can be controlled by either the BIOS 12 or the operating system 22. Additionally, a user may elect to disable the autoconfiguration component 28 in part or in whole,

allowing the user to manually configure the system 10.

In addition to the known functions of the system 10, the system includes a site locator 34 that is used to determine the identity of a remote site 38. The remote site is accessed via a network interface device 36 for
5 connecting the system 10 to a site that is unsupported by the system. The connection to the remote site is made via transmission lines 40, and the device 36 may be a modem or an interface to an ISDN or other digital network. In the preferred embodiment, the transmission lines are telecommunication lines, such as standard telephone lines, ISDN lines, T-1 lines, or
10 any other digital standard. The remote site may be one that is maintained by a vendor of the first device 16. As previously noted, the site that is identified by the site locator 34 includes software that is relevant to operation of the first device 16.

The site locator 34 "interrogates" the first device 16 that is
15 identified by the device locator 30. If the location information for identifying and accessing the remote site 38 is a telephone number of a publicly accessible bulletin board system (BBS), the telephone number is utilized to trigger the network interface device 36. On the other hand, if the remote site is a WWW site, a Web access program 42 of the system 10 is automatically
20 activated and used in conjunction with the network interface device 36 to access the site.

Referring now to Fig. 2, in a first step 44, a device is connected to the system. Remaining consistent with the example above, the first device 16 may be an adapter card that is inserted into a board slot to connect the
25 first device to the bus 14 of Fig. 1. When the system is then booted, a preliminary assignment of system resources is established at step 46. In step 48, the bus 14 is scanned and the add-on first device 16 is located and identified. Preferably, the device locator 30 of the autoconfiguration component 28 cooperates with both the BIOS 12 and the operating system
30 22 to identify the add-on device. Designers of devices for autoconfiguration capability build in an identifier within the device, using techniques known in the industry. However, the method of Fig. 2 requires a device designer to

also provide identification of the remote site 38 from which driver software specific to the first device 16 can be downloaded. At step 50 the location information is acquired by the site locator 34.

In one embodiment, the step 50 of identifying the remote site includes receiving data that is stored directly on the first device 16. In another embodiment, in addition to installing the hardware, the installation of the first device includes loading a computer disk that provides the required site location. The data contained on the disk is less likely to be "downlevel" than is the driver software that is conventionally packaged with the add-on hardware. The first embodiment in which the location information is stored in firmware is the preferred embodiment.

In step 52, the remote site is accessed using the transmission lines 40. As previously noted, possible network interface devices 36 for accessing the remote site 38 include modems and conventional interfaces to an ISDN or other digital network. While not critical, the method preferably includes an automated step of downloading 54 the device-level software. For the first device 16 of Fig. 1, this is a download of a latest version of a driver that is specific to the first device 16. The downloaded software is then installed 56. Again, this is preferably an automated step.

By automating at least some of steps 48-56, the user intervention in installing the device and installing a driver is reduced. Installing the latest version of driver software no longer requires expertise in contacting remote sites and downloading from those sites. Automating all of steps 48-56 frees a user from the burden typically associated with the installation process. Another advantage is that the user is ensured of installing the latest version of the device-level software for the device 16.

A determination of whether a second device is to be recognized is made at step 58. If a user has connected two devices at step 44, it will be necessary to repeat steps 48-56 for the second device. Repeating the steps is also required if the step 44 of connecting one or more devices is replaced with a step of upgrading the operating system to install a new version. A significant upgrade of the operating system may require a replacement of the

driver software for each of the devices 16, 18 and 20 in order to maximize performances of the individual devices.

If at step 58 the determination is made that no further device-level software is required, step 60 is a known step of autoconfiguring the system resources. This step is executed by the autoconfiguration component 28 of Fig. 1. An updated resource table 26 is then stored at the operating system level, and the process is ended 62. The user is then able to utilize any of the devices 16, 18 and 20.

As an alternative embodiment to Fig. 2, steps 48 and 50 may be steps in which all of the relevant devices and the appropriate remote sites are identified before the network is accessed for downloading software. In this embodiment, only one connection to the network is required, potentially providing savings with respect to time and/or connection costs.

While the invention has been described and illustrated primarily with respect to upgrading a personal computer, the invention may be used in other applications. The system and method may be utilized in any application in which there is sufficient sophistication to require an identification of a specific device and an association of the device with specific software.

Claims

1. A method of upgrading a system for supporting a plurality of devices comprising steps of:

locating a first device that is to be supported by said system;

5 as an automated response to locating said first device, determining location information relating to a remote site at which driver software specific to said first device is stored, said remote site being unsupported by said system;

10 as an automated response to determining said location information, accessing said remote site via transmission lines; and

downloading said driver software to said system from said remote site.

2. The method of claim 1 wherein said step of locating said first device is a step that is executed using techniques of plug-and-play technology.

3. The method of claim 1 wherein said step of determining said location information includes identifying an address within a network.

4. The method of claim 3 wherein said system is a personal computer and said step that includes identifying an address includes designating an Internet address, and wherein said step of accessing said remote site includes using telecommunications lines.

5 5. The method of claim 1 wherein said step of locating said first device includes detecting presence of a computer hardware device at a boot up of a computing system, said method further comprising a step of automatically installing said driver software after said step of downloading.

6. The method of claim 1 wherein said step of locating said first device is an automated response to one of either upgrading an operating system of a computer or detecting presence of an add-on device to said computer.

7. The method of claim 6 further comprising a step of autoconfiguring system resources following said step of downloading said driver software, said autoconfiguring being based upon resource requirements of said devices supported by said system.

8. The method of claim 1 wherein said step of determining location information is a step of designating information that identifies a site that is maintained by a manufacturer of said first device.

9. A method of initializing a device into a system comprising steps of:
installing said device into said system, including connecting
computer hardware and including providing system-accessible information identifying a remote site that relates to a supplier of said device;
5 in an absence of user intervention, initiating communication between said system and said remote site in response to said system accessing said system-accessible information, including utilizing telecommunication lines to establish said communications; and
exchanging data between said system and said remote site,
10 including exchanging data relating to operating said device within said system.

10. The method of claim 9 wherein said step of exchanging data includes downloading driver software from said remote site to said system.

11. The method of claim 10 wherein said step of downloading driver software is executed in an absence of user intervention.

12. The method of claim 9 wherein said step of initiating communication includes utilizing one of a modem or an interface to an ISDN or other digital network.

13. The method of claim 9 wherein said step of locating said first device includes detecting an adapter card of a computer system.

14. A system that is capable of autoconfiguration to accommodate support of a plurality of devices comprising:

means for identifying a first device of said plurality of devices;

5 site-detection means, responsive to said means of identifying, for detecting location information that designates a remote site unsupported by said system;

means, responsive to said site-detection means, for automatically accessing said remote site via transmission lines; and

10 storage means for receiving driver software downloaded from said remote site via said transmission lines.

15. The system of claim 14 wherein said means for automatically accessing said remote site is one of a modem or an interface to an ISDN or other digital network.

16. The system of claim 14 wherein said means for identifying, said site-detection means and said storage means are components of a computer system.

17. The system of claim 14 wherein said site-detection means is a means for identifying a network site maintained by a vendor of said first device.

18. The system of claim 14 further comprising means for automatically initiating an allocation of system resources to said first device partially based upon said downloaded driver software.

19. A method of automatically refreshing driver software of a device supported by a system, said method comprising steps of:

in response to a determination that said device is operating improperly, requesting that driver software specific to said device be
5 acquired;

as an automated response to said request, identifying a remote network site at which said driver software can be downloaded;

as an automated response to said identification of said remote network site, accessing said site via telecommunications lines and
10 downloading said driver software; and

installing said downloaded driver software.




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

Int .ional Application No

PCT/US 98/27924

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06F9/445

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	US 5 870 610 A (BEYDA WILLIAM J) 9 February 1999 (1999-02-09) the whole document	1-19
A	EP 0 632 629 A (MULTI TECH SYSTEMS INC) 4 January 1995 (1995-01-04) abstract page 2, line 24 - line 35 page 6, line 23 - page 7, line 1 claims 1,11,12	1,9,14, 19
A	WO 96 04603 A (IBM) 15 February 1996 (1996-02-15) abstract page 2, line 5 - line 21	1,9,14, 19
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
 "E" earlier document but published on or after the international filing date
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 "O" document referring to an oral disclosure, use, exhibition or other means
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
 "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
 "&" document member of the same patent family

Date of the actual completion of the international search

5 August 1999

Date of mailing of the international search report

13/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Wiltink, J

INTERNATIONAL SEARCH REPORT

Int .onal Application No

PCT/US 98/27924

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 598 511 A (CANON INFORMATION SYST INC) 25 May 1994 (1994-05-25) abstract page 2, line 45 - page 3, line 7 page 24, line 42 - page 25, line 45 page 28, line 7 - line 51 claims 1,10 ---	1,9,14, 19
P,A	US 5 655 148 A (RICHTMAN DARRYL STEVEN ET AL) 5 August 1997 (1997-08-05) abstract column 3, line 23 - column 10, line 54 -----	1,9,14, 19

INTERNATIONAL SEARCH REPORT

Information on patent family members

In .ional Application No

PCT/US 98/27924

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5870610	A	09-02-1999	NONE	
EP 0632629	A	04-01-1995	CA 2126926 A JP 7147611 A US 5644594 A	03-01-1995 06-06-1995 01-07-1997
WO 9604603	A	15-02-1996	US 5668992 A BR 9502940 A CA 2150742 A CN 1128373 A CZ 9700253 A DE 69503056 D DE 69503056 T EP 0774136 A HU 77153 A JP 8055018 A PL 318373 A	16-09-1997 21-05-1996 02-02-1996 07-08-1996 17-12-1997 23-07-1998 18-02-1999 21-05-1997 02-03-1998 27-02-1996 09-06-1997
EP 0598511	A	25-05-1994	US 5815722 A JP 6214929 A	29-09-1998 05-08-1994
US 5655148	A	05-08-1997	US 5787246 A US 5748980 A US 5793979 A US 5819107 A US 5809329 A	28-07-1998 05-05-1998 11-08-1998 06-10-1998 15-09-1998